

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for shifting a perspective ~~in~~of a composite image derived from a plurality of component images including a first image and a second image, the composite image including the first image as a center of projection and a modified version of the second image, the modified version of the second image having been corrected for perspective distortion relative to the first image, the method comprising:

receiving an instruction to shift the perspective of the composite image to make the second image the center of projection ~~of the composite image~~;

determining a transformation for mapping a set of reference points in the modified version of the second image to a corresponding set of reference points in the second image; and

applying the transform to each of the plurality of derived component images in the composite image to generate a plurality of transformed component images, each of the transformed component images having the second image as their center of projection.

2. (Original) The method of claim 1, further comprising:

merging the modified version of the first image and the second image to form a second composite image that has the second image as its center of projection.

3. (Original) The method of claim 1, wherein the plurality of images includes a third image and the composite image includes a first modified version of the third image, the first modified version of the third image being corrected for perspective distortion relative to the first image, the method further comprising:

transforming the first modified version of the third image based on the transformation to derive a second modified version of the third image, the second modified version of the third image being corrected for perspective distortion relative to the second image; and

merging the modified version of the first image, the second image, and the second modified version of the third image to form a second composite image.

4. (Original) The method of claim 1, wherein:

the reference points in the modified version of the second image include four non-collinear and non-coincident points in the modified version of the second image; and

the reference points in the second image include four non-collinear and non-coincident points in the second image.

5. (Original) The method of claim 1, wherein:

the second image and the modified version of the second image each include a perimeter; and

the reference points in the second image and the modified version of the second image are vertices on the perimeters of the second image and the modified version of the second image.

6. (Original) The method of claim 5, wherein:

the first image includes a plurality of pixels and has a perimeter that defines a set of vertices; and

transforming the first image based on the transformation includes:

transforming the vertices of the first image; and

transforming the pixels of the first image based on the transformation of the vertices.

7. (Original) The method of claim 6, wherein:
the transformation is represented as a transformation matrix.
8. (Original) The method of claim 7, wherein:
the transformation matrix is derived from the vertices of the modified version of the second image.
9. (Original) The method of claim 8, wherein:
the transformation matrix is further derived from the vertices of the second image.
10. (Original) The method of claim 9, wherein the transformation matrix, M , is given by:

$$M = \begin{bmatrix} q_4 - q_5q_7 & q_5q_6 - q_3 & q_3q_7 - q_4q_6 \\ q_2q_7 - q_1 & q_0 - q_2q_6 & q_1q_6 - q_0q_7 \\ q_1q_5 - q_2q_4 & q_2q_3 - q_0q_5 & q_0q_4 - q_1q_3 \end{bmatrix}$$

where:

$$\begin{bmatrix} q_0 \\ q_1 \\ q_2 \\ q_3 \\ q_4 \\ q_5 \\ q_6 \\ q_7 \end{bmatrix} = \begin{bmatrix} u_0 & v_0 & 1 & 0 & 0 & 0 & -u_0x_0 & -v_0x_0 \\ u_1 & v_1 & 1 & 0 & 0 & 0 & -u_1x_1 & -v_1x_1 \\ u_2 & v_2 & 1 & 0 & 0 & 0 & -u_2x_2 & -v_2x_2 \\ u_3 & v_3 & 1 & 0 & 0 & 0 & -u_3x_3 & -v_3x_3 \\ 0 & 0 & 0 & u_0 & v_0 & 1 & -u_0y_0 & -v_0y_0 \\ 0 & 0 & 0 & u_1 & v_1 & 1 & -u_1y_1 & -v_1y_1 \\ 0 & 0 & 0 & u_2 & v_2 & 1 & -u_2y_2 & -v_2y_2 \\ 0 & 0 & 0 & u_3 & v_3 & 1 & -u_3y_3 & -v_3y_3 \end{bmatrix}^{-1} \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ y_0 \\ y_1 \\ y_2 \\ y_3 \end{bmatrix}$$

$(u_0, v_0), (u_1, v_1), (u_2, v_2), (u_3, v_3)$ are coordinates of vertices of the second image,

and

$(x_0, y_0), (x_1, y_1), (x_2, y_2), (x_3, y_3)$ are coordinates of vertices of the modified

version of the second image.

11. (Original) The method of claim 1, wherein:
 - the reference points in the modified version of the second image are corner points on a trapezoid formed by a perimeter of the modified version of the second image; and
 - the reference points in the second image are corner points on a rectangle formed by a perimeter of the second image.
12. (Original) The method of claim 1, wherein:
 - transforming the modified version of the second image alters the shape of a perimeter of the modified version of the second image by moving at least one reference point relative to at least one other reference point.
13. (Original) The method of claim 1, wherein:
 - the modified version of the second image has a perimeter forming a trapezoid; and
 - transforming the modified version of the second image alters the perimeter of the modified version of the second image to form a rectangle.
14. (Original) The method of claim 1, wherein:
 - the instruction to shift perspective is received as a single user input; and
 - the determining and transforming steps are automatically performed in response to the user input.

15. (Currently Amended) A computer-implemented image processing method, comprising:
- providing a composite image derived from a plurality of component images including a first image and a second image, the composite image including the first image as a center of projection and a modified version of the second image, the modified version of the second image having been corrected for perspective distortion relative to the first image;
 - receiving a single user input including an instruction to change ~~the~~ a perspective of the composite image to make the second image the center of projection; and
 - in response to the input, automatically:
 - determining a transformation for mapping a set of reference points in the modified version of the second image to a set of reference points in the second image;
 - applying the transform to each of the plurality of derived component images in the composite image to generate a plurality of transformed component images, each of the transformed component images having the second image as their center of projection, each of the transformed component images being corrected for perspective distortion relative to the second image; and
 - merging the second image and the plurality of the transformed component images corrected for perspective distortion relative to the second image to form a second composite image that has the second image as its center of projection.

16. (Currently Amended) A computer program product, tangibly stored on a computer-readable medium, for shifting a perspective of ~~in~~ a composite image derived from a plurality of component images including a first image and a second image, the composite image including the first image as a center of projection and a modified version of the second image, the modified version of the second image having been corrected for perspective distortion relative to the first image, the product comprising instructions operable to cause a programmable processor to:

receive an instruction to shift the perspective of the composite image to make the second image the center of projection ~~of the composite image~~;

determine a transformation for mapping a set of reference points in the modified version of the second image to a corresponding set of reference points in the second image; and

apply the transform to each of the plurality of derived component images in the composite image to generate a plurality of transformed component images, each of the transformed component images having the second image as their center of projection.

17. (Original) The computer program product of claim 16, further comprising instructions operable to cause a programmable processor to:

merge the modified version of the first image and the second image to form a second composite image that has the second image as its center of projection.

18. (Original) The computer program product of claim 16, wherein the plurality of images includes a third image and the composite image includes a first modified version of the third image, the first modified version of the third image being corrected for perspective distortion relative to the first image, the product further comprising instructions operable to cause a programmable processor to:

transform the first modified version of the third image based on the transformation to derive a second modified version of the third image, the second modified version of the third image being corrected for perspective distortion relative to the second image; and

merge the modified version of the first image, the second image, and the second modified version of the third image to form a second composite image.

19. (Original) The computer program product of claim 16, wherein:
the reference points in the modified version of the second image include four non-collinear and non-coincident points in the modified version of the second image; and
the reference points in the second image include four non-collinear and non-coincident points in the second image.
20. (Original) The computer program product of claim 16, wherein:
the second image and the modified version of the second image each include a perimeter;
and
the reference points in the second image and the modified version of the second image are vertices on the perimeters of the second image and the modified version of the second image.
21. (Original) The computer program product of claim 20, wherein:
the first image includes a plurality of pixels and has a perimeter that defines a set of vertices; and
the instructions operable to cause a programmable processor to transform the first image based on the transformation include instructions operable to cause a programmable processor to:
transform the vertices of the first image; and
transform the pixels of the first image based on the transformation of the vertices.
22. (Original) The computer program product of claim 21, wherein:
the transformation is represented as a transformation matrix.
23. (Original) The computer program product of claim 22, wherein:
the transformation matrix is derived from the vertices of the modified version of the second image.
24. (Original) The computer program product of claim 23, wherein:
the transformation matrix is further derived from the vertices of the second image.

25. (Original) The computer program product of claim 24, wherein the transformation matrix, M , is given by:

$$M = \begin{bmatrix} q_4 - q_5q_7 & q_5q_6 - q_3 & q_3q_7 - q_4q_6 \\ q_2q_7 - q_1 & q_0 - q_2q_6 & q_1q_6 - q_0q_7 \\ q_1q_5 - q_2q_4 & q_2q_3 - q_0q_5 & q_0q_4 - q_1q_3 \end{bmatrix}$$

where:

$$\begin{bmatrix} q_0 \\ q_1 \\ q_2 \\ q_3 \\ q_4 \\ q_5 \\ q_6 \\ q_7 \end{bmatrix} = \begin{bmatrix} u_0 & v_0 & 1 & 0 & 0 & 0 & -u_0x_0 & -v_0x_0 \\ u_1 & v_1 & 1 & 0 & 0 & 0 & -u_1x_1 & -v_1x_1 \\ u_2 & v_2 & 1 & 0 & 0 & 0 & -u_2x_2 & -v_2x_2 \\ u_3 & v_3 & 1 & 0 & 0 & 0 & -u_3x_3 & -v_3x_3 \\ 0 & 0 & 0 & u_0 & v_0 & 1 & -u_0y_0 & -v_0y_0 \\ 0 & 0 & 0 & u_1 & v_1 & 1 & -u_1y_1 & -v_1y_1 \\ 0 & 0 & 0 & u_2 & v_2 & 1 & -u_2y_2 & -v_2y_2 \\ 0 & 0 & 0 & u_3 & v_3 & 1 & -u_3y_3 & -v_3y_3 \end{bmatrix}^{-1} \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ y_0 \\ y_1 \\ y_2 \\ y_3 \end{bmatrix}$$

$(u_0, v_0), (u_1, v_1), (u_2, v_2), (u_3, v_3)$ are coordinates of vertices of the second image,

and

$(x_0, y_0), (x_1, y_1), (x_2, y_2), (x_3, y_3)$ are coordinates of vertices of the modified

version of the second image.

26. (Original) The computer program product of claim 16, wherein:

the reference points in the modified version of the second image are corner points on a trapezoid formed by a perimeter of the modified version of the second image; and

the reference points in the second image are corner points on a rectangle formed by a perimeter of the second image.

27. (Original) The computer program product of claim 16, wherein:
the instructions operable to cause a programmable processor to transform the modified version of the second image are operable to cause the programmable processor to alter the shape of a perimeter of the modified version of the second image by moving at least one reference point relative to at least one other reference point.
28. (Original) The computer program product of claim 16, wherein:
the modified version of the second image has a perimeter forming a trapezoid; and
the instructions operable to cause a programmable processor to transform the modified version of the second image are operable to cause the programmable processor to alter the perimeter of the modified version of the second image to form a rectangle.
29. (Previously Presented) The computer program product of claim 16 wherein:
the instruction to shift perspective is received as a single user input; and
the product includes instructions to cause the programmable processor to determine the transformation and transform the images automatically in response to the user input.

30. (Currently Amended) A computer program product, tangibly stored on a computer-readable medium, for processing an image, comprising instructions operable to cause a programmable processor to:

receive a composite image derived from a plurality of component images including a first image and a second image, the composite image including the first image as a center of projection and a modified version of the second image, the modified version of the second image having been corrected for perspective distortion relative to the first image;

receive a single user input including an instruction to change ~~the~~ a perspective of the composite image to make the second image the center of projection; and

in response to the input, automatically:

determine a transformation for mapping a set of reference points in the modified version of the second image to a set of reference points in the second image;

apply the transform to each of the plurality of derived component images in the composite image to generate a plurality of transformed component images, each of the transformed component images having the second image as their center of projection, each of the transformed component images being corrected for perspective distortion relative to the second image; and

merge the second image and the plurality of transformed component images corrected for perspective distortion relative to the second image to form a second composite image that has the second image as its center of projection.